

Features:

- Microphone anti static shock protection
- Stylish, comfortable and durable
- Noise cancelling microphone
- Acoustic Shock protection
- Voice qualified technology
- Soft & durable headband T-bar
- Single wire on mono and binaural versions



The professional choice in headset technology

DH-036TFN - an elegant headband style

Lightweight, stylish and robust design for exceptional comfort and durability.

Flexible microphone boom adjusts for the best voice transmission

270° rotating microphone boom arm

Available from:

INCLUDES:

Headset, Quick Disconnect curly cord, headset hook, headset bag and spare foam ear cushion
Wideband receiver is especially suitable for IP & UC applications.
Compatible with desk phones, IP phones, MS Lync, Skype, mobile and softphones.

Optional connections include:

- 2.5mm jack
- 3.5mm jack
- Plantronics wiring
- GN wiring
- USB connection

Technical Data:

Electrical Characteristics (EARPHONE)

- Impedance - 150ohm
- Sensitivity - 92dB \pm 3dB at 1KHz 60mV input
- Max. input power - 100mW
- Frequency range 300Hz - 5KHz
- Distortion - less 3% at 1 KHz 60mV

Electrical Characteristics (MIC)

- Sensitivity @ 1KHz - 32dB \pm 3dB
- Impedance - 2.2ohm
- Directivity - Noise cancellation microphone
- Frequency range - 200Hz to 7.5KHz
- Distortion - less than 3%
- S/N/Ration - More than 58dB

